

Docket No. AUS920030165US1

PRIVATE SOURCE CODE COMMENTING

BACKGROUND OF THE INVENTION

5 **1. Technical Field:**

 The present invention is related to computer-aided software engineering (CASE) tools for collaborative software development.

10 **2. Description of Related Art:**

 "Software engineering" is the practice of software development as an industrial discipline. The goal of Software Engineering is to produce high-quality, maintainable software through an efficient use of development resources.

 Most commercially-developed software is developed by teams of programmers. Very large software projects may require a large number of programmers or a large number of teams of programmers. One area of particular interest to Software Engineering is the interaction between members of a programming team and between programmers and management.

 Conventional Software Engineering wisdom suggests that the task of producing a software product is best practiced by conceptualizing the product as a system of interrelated components, dividing the components among members of a programming team, having team members work in parallel to produce the components, and assembling the components into a working system. In other words,

Docket No. AUS920030165US1

conventional wisdom suggests a "divide-and-conquer" approach to software development.

D.B. Simmons, "Communications: a software group productivity dominator," IEEE Software Engineering Journal, November 1991, pp. 454-462, for example, takes the position that a system design that is poorly partitioned will result in a large amount of inter-programmer communication to resolve dependency issues, which ultimately degrades productivity. In an ideal divide-and-conquer situation, inter-programmer communication should be unnecessary, so any time spent communicating, rather than on writing source lines of code (SLOC), degrades productivity. Simmons thus advocates employing careful system design and small team sizes to minimize communication between programmers, the ultimate goal being to approach an ideal "divide-and-conquer" scenario.

A dramatically different approach to inter-programmer communication can be found in the increasingly popular Software Engineering methodology known as "eXtreme Programming" (XP), which was founded by Ken Beck. XP is based on team collaboration on all phases of a software development project, rather than a pure divide-and-conquer approach. XP emphasizes continuous communication between members of a programming team, with the theory being that when all members of a team are familiar with the project as a whole, a project design can evolve as needed to resolve whatever issues may arise during the implementation phase of a project, such as dependency and integration issues. Thus, the XP

Docket No. AUS920030165US1

methodology includes such concepts as common code ownership, in which all team members are allowed to work on any portion of the project.

Although divide-and-conquer and XP represent two
5 very different approaches to software development, these two methodologies highlight the significant role that inter-programmer communication plays in a large software project. Two overarching principles come to mind: First, communication between team members is essential, because
10 in a practical setting, dependency and integration issues between different programmers' work will invariably arise. Second, it is important to productivity that communication between team members is efficient. A design that is well-planned (as advocated in Simmons' article) or at least well-understood (as advocated in
15 XP), can help in this respect.

Computer-Aided Software Engineering (CASE) is the sub-field of Software Engineering that is concerned with developing software tools (called "CASE tools") for
20 making software development more efficient and less error-prone. A number of existing CASE technologies are directed to problems relating to team software development, including communication between developers. Several of these are discussed below.

25 A number of configuration management tools exist in the art. Configuration management tools allow different versions (configurations) of a file to be maintained, so that a permanent copy of an earlier version of a file under modification can be maintained. These kinds of
30 tools are very helpful in software development for

Docket No. AUS920030165US1

maintaining different versions of source code files under development, because working or "stable" versions of source code files can be maintained while newer versions are being developed. Many configuration management tools
5 also allow a "snapshot" of a group of source files to be made, so that a particular point in time of an entire software development project may be recorded.

Most modern configuration management tools also allow multiple users to "check out" files and "check in"
10 modified versions of files, to ensure consistency of file versions for multiple users. Generally, a configuration management tool will keep a "log" so that comments regarding the changes made between versions can be recorded. Some configuration management tools, such as
15 the open-source Concurrent Versioning System (CVS), allow for distributed access to a group of source files (i.e., they allow developers to access the files from remote computers on a network, such as the Internet). Revision Control System (RCS) is another popular open-source
20 configuration management tool.

Some existing tools provide more extensive features for collaborative programming than do simple configuration management systems. Some of these tools are network- or World-Wide Web-based. For example,
25 SOURCEFORGE™ is a trademark for a collaborative software development system produced by VA Software Corporation of Fremont, California. The SOURCEFORGE™ collaborative software development system is used by a number of organizations to support collaborative software
30 development on organizational intranets using a web-based

Docket No. AUS920030165US1

interface. The SOURCEFORGE™ collaborative software development system also forms the basis for "SOURCEFORGE™.net," which is reportedly the world's largest open-source development website.

5 Open-source software, particularly in recent times, is often a collaborative product of multiple developers working in remote locations over the Internet. The open-source Linux operating system, for example, was created by Linus Torvalds (for whom Linux is named) in Finland.
10 Many enhancements to Linux, such as device drivers, have been contributed by programmers worldwide through the Internet.

 SOURCEFORGE™.net supports a number of features that are conducive to collaborative programming over a wide-
15 area network (WAN), such as the Internet. On SOURCEFORGE™.net, each open-source programming project is given a web page that includes a number of communication features for communicating with developers and users of open-source software products. "Trackers" are provided
20 to allow users or developers to report bugs, request new features to be added to a program, or request technical support. Other, more general discussion forums, including a public message forum, mailing lists, and a news archive are also provided. A task manager
25 application is provided for project planning and delegation of tasks among developers. Source code or binary releases of a software product may be downloaded from that product's SOURCEFORGE™.net page or from one of a number of mirror sites.

Docket No. AUS920030165US1

A developer (or user, for that matter) may also use the CVS configuration management system to "mount" to the project's code repository and download any version of the source code (including the latest "under development" sources). CVS may also be used by a developer having appropriate privileges to check out or check in source code files for inclusion in the project. SOURCEFORGE™.net also includes a "compile farm" for compiling and testing software on various platforms (e.g., that a particular developer might not have access to, otherwise).

Most computer languages have some facility for leaving (non-executable) comments in program code. For example, in the "C" programming language, comments are written between "slash-star" and "star-slash" delimiters (e.g., /* comment */). Some programming languages allow for more advanced commenting features. The JAVA™ programming language (a trademark of Sun Microsystems, Inc.) allows special "javadoc" comments that can be associated with particular classes, fields, or methods in a JAVA™ programming language source file. "javadoc" comments may include special tags to provide program documentation in a structured format. A tool, called "javadoc," is provided in Sun Microsystems' JAVA™ 2 Software Development Kit (J2SDK), which can compile the javadoc comments into specially-formatted Hypertext Markup Language (HTML) source for display in a web browser. The open-source Perl programming language version 5 (Perl 5), developed by Larry Wall, includes a similar feature to javadoc, called "POD," which stands for "plain old documentation."

Docket No. AUS920030165US1

The open-source Python programming language, developed by Guido van Rossum, includes a feature known as "doc strings." "Doc strings" are special strings, denoted by triple quotation marks, that are used to describe particular objects or functions in Python. Unlike ordinary comments, however, "doc strings" are available to a Python program at run-time. Because Python has an interactive mode to allow code to be entered and executed at an interpreter prompt, the ability to read program comments at run-time is particularly valuable in Python.

Literate programming is a programming methodology originated by Turing Award winner Prof. Donald Knuth of Stanford University. Literate programming is based on the idea that well-written program code should be written to be read by others. Knuth created the WEB programming system for literate programming in Pascal. WEB allows a programmer to write code in sections, in which each section contains a descriptive subsection for entering a natural language description of a portion of code, a macro section for defining macros, and a code section for entering Pascal code. The macro features of WEB allow a programmer to write code for presentation to a reader in any particular order.

WEB is made up of two programs, TANGLE and WEAVE, each of which processes a WEB source file. WEAVE formats the text documentation and pretty-prints the code in a format suitable for processing by Knuth's typesetting program TeX (which, incidentally, was written using WEB). TANGLE, on the other hand, removes the text documentation

Docket No. AUS920030165US1

and performs macro substitutions to arrive at source code suitable for compilation by a Pascal compiler.

A number of literate programming tools have been developed for other languages. Some of these are
5 patterned after Knuth's original WEB program, such as CWEB for literate programming in C, and FWEB for literate programming in Fortran. A number of language-independent literate programming tools are also available.

Thus, configuration management tools aid in the
10 management of team programming projects by providing some degree of concurrency control and transaction management (in the database-management sense), and advanced documentation features, such as are provided in literate programming tools, make program code easier for others to
15 understand. Both of these CASE technologies are a boon to software developers and software development teams, because they help developers collaborate effectively to manage complexity. In very large software projects, however, the process of collaborating itself may become
20 quite complex.

Whether one views inter-developer communication as an unavoidable and necessary evil or as something to be encouraged the fact remains that communication needs to be efficient and effective. If too much information is
25 exchanged, information overload can result and productivity and quality are compromised. On the other hand, when information is less freely exchanged, the process of acquiring and disseminating necessary information may become inefficient.

Docket No. AUS920030165US1

There is a need, then, for an efficient form of information exchange between software developers working on a common project.

SUMMARY OF THE INVENTION

The present invention provides a method, computer program product, and data processing system for exchanging information regarding software source code among a team of developers. In a preferred embodiment of the present invention, a developer associates commentary with a particular code feature, such as a function or object class. A list of intended recipients or readers of the commentary is obtained from the developer. Additional settings regarding such things as an expiration date for the commentary are also obtained from the developer. The source code with associated commentary is then made available to the intended readers. If desired, the source code with associated commentary may be transmitted the intended recipients via e-mail or an "instant message" or other form of notification can be transmitted to the intended recipients to notify them of the commentary to be read.

20 The present invention may be embodied as part of an integrated development environment (IDE), in which an editor program and other programming tools (e.g., compilers, linkers, debuggers, etc.) are presented to the developer using a common interface (or in a common executable). Alternatively, the present invention may be embodied in a command-line style development tool, much like the "cc" and "make" command-line tools used in POSIX-based operating systems (POSIX stands for "Portable Operating System Interface, which is the name given to a family of operating system standards developed by IEEE,

Docket No. AUS920030165US1

the Institute for Electrical and Electronics Engineers).
The present invention may also be combined with
configuration management software.

BRIEF DESCRIPTION OF THE DRAWINGS

The novel features believed characteristic of the invention are set forth in the appended claims. The invention itself, however, as well as a preferred mode of use, further objectives and advantages thereof, will best be understood by reference to the following detailed description of an illustrative embodiment when read in conjunction with the accompanying drawings, wherein:

10 **Figure 1** is a diagram of a networked data processing system in which the present invention may be implemented;

Figure 2 is a block diagram of a server system within the networked data processing system of **Figure 1**;

Figure 3 is a block diagram of a client system
15 within the networked data processing system of **Figure 1**;

Figure 4 is a use case diagram depicting use cases applicable to a preferred embodiment of the present invention;

Figures 5-7 are deployment diagrams depicting
20 various ways of deploying a source code private commenting system in accordance with a preferred embodiment of the present invention;

Figure 8 is a deployment diagram depicting the use of electronic mail notification of source code commentary
25 in accordance with a preferred embodiment of the present invention;

Figure 9 is a collaboration diagram depicting a process of producing and disseminating private source code commentary in accordance with a preferred embodiment
30 of the present invention;

Docket No. AUS920030165US1

Figure 10 is a flow diagram depicting a process of storing commentary in accordance with a preferred embodiment of the present invention;

5 **Figure 11** is a flow diagram depicting a process of displaying commentary directed to a specific user in accordance with a preferred embodiment of the present invention;

10 **Figure 12** is a flow diagram depicting a process of generating commented source code and object code from a combined file in accordance with a preferred embodiment of the present invention;

15 **Figure 13** is a diagram depicting a portion of a source code document in which markup language tags are included to associate developer commentary with program code in accordance with a preferred embodiment of the present invention;

20 **Figure 14** is a diagram depicting a portion of a source code document in which an additional constraint on a particular item of commentary is placed through the use of a markup tag attribute;

Figure 15 is a screenshot diagram of an integrated development environment in which private source code commentary is being defined in accordance with a preferred embodiment of the present invention;

25 **Figure 16** is a screenshot of an integrated development environment in which source code commentary is being associated with a group of intended readers in accordance with a preferred embodiment of the present invention; and

Docket No. AUS920030165US1

Figure 17 is a flowchart representation of a process of creating and disseminating private source code commentary in accordance with a preferred embodiment of the present invention.

Docket No. AUS920030165US1

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

With reference now to the figures, **Figure 1** depicts a pictorial representation of a network of data processing systems in which the present invention may be implemented. Network data processing system **100** is a network of computers in which the present invention may be implemented. Network data processing system **100** contains a network **102**, which is the medium used to provide communications links between various devices and computers connected together within network data processing system **100**. Network **102** may include connections, such as wire, wireless communication links, or fiber optic cables.

In the depicted example, server **104** is connected to network **102** along with storage unit **106**. In addition, clients **108**, **110**, and **112** are connected to network **102**. These clients **108**, **110**, and **112** may be, for example, personal computers or network computers. In the depicted example, server **104** provides data, such as boot files, operating system images, and applications to clients **108-112**. Clients **108**, **110**, and **112** are clients to server **104**. Network data processing system **100** may include additional servers, clients, and other devices not shown. In the depicted example, network data processing system **100** is the Internet with network **102** representing a worldwide collection of networks and gateways that use the Transmission Control Protocol/Internet Protocol (TCP/IP) suite of protocols to communicate with one another. At the heart of the Internet is a backbone of high-speed data communication lines between major nodes or host computers,

Docket No. AUS920030165US1

consisting of thousands of commercial, government, educational and other computer systems that route data and messages. Of course, network data processing system **100** also may be implemented as a number of different types of networks, such as for example, an intranet, a local area network (LAN), or a wide area network (WAN). **Figure 1** is intended as an example, and not as an architectural limitation for the present invention.

Referring to **Figure 2**, a block diagram of a data processing system that may be implemented as a server, such as server **104** in **Figure 1**, is depicted in accordance with a preferred embodiment of the present invention. Data processing system **200** may be a symmetric multiprocessor (SMP) system including a plurality of processors **202** and **204** connected to system bus **206**. Alternatively, a single processor system may be employed. Also connected to system bus **206** is memory controller/cache **208**, which provides an interface to local memory **209**. I/O bus bridge **210** is connected to system bus **206** and provides an interface to I/O bus **212**. Memory controller/cache **208** and I/O bus bridge **210** may be integrated as depicted.

Peripheral component interconnect (PCI) bus bridge **214** connected to I/O bus **212** provides an interface to PCI local bus **216**. A number of modems may be connected to PCI local bus **216**. Typical PCI bus implementations will support four PCI expansion slots or add-in connectors. Communications links to clients **108-112** in **Figure 1** may be provided through modem **218** and network adapter **220** connected to PCI local bus **216** through add-in boards.

Docket No. AUS920030165US1

Additional PCI bus bridges **222** and **224** provide interfaces for additional PCI local buses **226** and **228**, from which additional modems or network adapters may be supported. In this manner, data processing system **200**
5 allows connections to multiple network computers. A memory-mapped graphics adapter **230** and hard disk **232** may also be connected to I/O bus **212** as depicted, either directly or indirectly.

Those of ordinary skill in the art will appreciate
10 that the hardware depicted in **Figure 2** may vary. For example, other peripheral devices, such as optical disk drives and the like, also may be used in addition to or in place of the hardware depicted. The depicted example is not meant to imply architectural limitations with respect
15 to the present invention.

The data processing system depicted in **Figure 2** may be, for example, an IBM eServer pSeries system, a product of International Business Machines Corporation in Armonk, New York, running the Advanced Interactive Executive
20 (AIX) operating system or LINUX operating system.

With reference now to **Figure 3**, a block diagram illustrating a data processing system is depicted in which the present invention may be implemented. Data processing system **300** is an example of a client computer. Data
25 processing system **300** employs a peripheral component interconnect (PCI) local bus architecture. Although the depicted example employs a PCI bus, other bus architectures such as Accelerated Graphics Port (AGP) and Industry Standard Architecture (ISA) may be used.
30 Processor **302** and main memory **304** are connected to PCI

Docket No. AUS920030165US1

local bus **306** through PCI bridge **308**. PCI bridge **308** also may include an integrated memory controller and cache memory for processor **302**. Additional connections to PCI local bus **306** may be made through direct component
5 interconnection or through add-in boards. In the depicted example, local area network (LAN) adapter **310**, SCSI host bus adapter **312**, and expansion bus interface **314** are connected to PCI local bus **306** by direct component connection. In contrast, audio adapter **316**, graphics
10 adapter **318**, and audio/video adapter **319** are connected to PCI local bus **306** by add-in boards inserted into expansion slots. Expansion bus interface **314** provides a connection for a keyboard and mouse adapter **320**, modem **322**, and additional memory **324**. Small computer system interface
15 (SCSI) host bus adapter **312** provides a connection for hard disk drive **326**, tape drive **328**, and CD-ROM drive **330**. Typical PCI local bus implementations will support three or four PCI expansion slots or add-in connectors.

An operating system runs on processor **302** and is used
20 to coordinate and provide control of various components within data processing system **300** in **Figure 3**. The operating system may be a commercially available operating system, such as the WINDOWS XP operating system, which is available from Microsoft Corporation. An object oriented
25 programming system such as JAVA™ may run in conjunction with the operating system and provide calls to the operating system from programs or applications executing on data processing system **300**. "JAVA" is a trademark of Sun Microsystems, Inc. Instructions for the operating
30 system, the object-oriented operating system, and

Docket No. AUS920030165US1

applications or programs are located on storage devices, such as hard disk drive **326**, and may be loaded into main memory **304** for execution by processor **302**.

Those of ordinary skill in the art will appreciate
5 that the hardware in **Figure 3** may vary depending on the implementation. Other internal hardware or peripheral devices, such as flash read-only memory (ROM), equivalent nonvolatile memory, or optical disk drives and the like, may be used in addition to or in place of the hardware
10 depicted in **Figure 3**. Also, the processes of the present invention may be applied to a multiprocessor data processing system.

As another example, data processing system **300** may be a stand-alone system configured to be bootable without
15 relying on some type of network communication interfaces. As a further example, data processing system **300** may be a personal digital assistant (PDA) device, which is configured with ROM and/or flash ROM in order to provide non-volatile memory for storing operating system files
20 and/or user-generated data.

The depicted example in **Figure 3** and above-described examples are not meant to imply architectural limitations. For example, data processing system **300**
also may be a notebook computer or hand held computer in
25 addition to taking the form of a PDA. Data processing system **300** also may be a kiosk or a Web appliance.

The present invention provides a method, computer program product, and data processing system for exchanging information regarding software source code
30 intended for limited distribution among a team of

Docket No. AUS920030165US1

software developers. **Figure 4** is a use case diagram depicting particular user-directed actions (use cases) that can be performed by a preferred embodiment of the present invention. **Figure 4**, like many of the other
5 diagrams in this document, is patterned after the Uniform Modeling Language (UML), an open standard for object-oriented modeling of systems. It should be noted, however, that this document does not strictly follow the UML standard.

10 Now turning to the content of **Figure 4**, commenting system **400** represents a preferred embodiment of the present invention. User **402** is a software developer using commenting system **400**.

This document makes extensive use of the term
15 "developer." Although a developer, as the term is used in the art, is generally a programmer (i.e., someone who writes program code), the term "developer" should be interpreted more broadly in this document. In the present context, the term "developer" is used to mean
20 someone who may potentially view all or part of the source code to a software product.

One of ordinary skill will recognize that this definition of "developer" encompasses not only programmers, but other parties, as well. Some examples
25 of "non-programmer developers" of a software product include software architects, members of management, software testers, intellectual property attorneys, consultants, system administrators, and the like. In some instances, the actual users of a software product
30 may be considered "developers," as well, since in the

Docket No. AUS920030165US1

case of some software products, customers, clients, or other end users are supplied with source code. In the case of open-source software, for example, sometimes an end user is provided with *only* the source code and must
5 compile the source code into an executable form. In these situations it may be necessary for an end user to edit or at least view the source code in order to configure or modify the source code for the purpose of making the source code compile on a particular target
10 machine or for the purpose of enabling or implementing optional or novel features in a software product.

Use cases **404-410** represent actions that user **402** may use commenting system **400** to perform. Commenting system **400** may be integrated or embedded into another
15 tool such an integrated development environment (IDE) or editor. In particular, some editor programs, such as the widely-used open-source EMACS editor developed by Richard Stallman, are extensible in the sense that they include a facility for a user to program additional features into
20 the editor application. For example, EMACS includes its own dialect of the LISP programming language, with which a user may program additional features as desired.

Alternatively, commenting system **400** may take the form of a standalone program or be embedded into a
25 individual programming tool or a suite of tools. For example, commenting system **400** may be embedded within a configuration management system, such as the open-source configuration management tools RCS (Revision Control System) or CVS (Concurrent Versioning System), which are
30 generally executed using a command-line interface in a

Docket No. AUS920030165US1

POSIX-type operating system. POSIX stands for "Portable Operating System Interface, which is the name given to a family of operating system standards developed by IEEE, the Institute for Electrical and Electronics Engineers.

- 5 AIX (Advanced Interactive executive), an IBM Corporation product, is an example of a POSIX-based operating system.

User **402** may associate a comment with a source code feature in a body of source code being edited or examined by user **402** (use case **404**). "Source code" is computer
10 program code that is in a form that can be edited by a developer. In the paradigmatic case of compiled languages such as C or an assembly language, source code will generally be made up of one or more text files (strictly speaking, assembly language is "assembled," but
15 one of ordinary skill in the art will recognize that assembly may be thought of as a special case of compilation).

In this document, the term "source code" also includes code that is intended to be executed by an
20 interpreter. Further, other non-text documents may also be considered "source code" for the purposes of this document. For example, class diagrams, state charts, and other graphical forms for representing software are also "source code" for the purposes of this document, since,
25 in many cases, such diagrams may be translated or compiled into source code in a conventional programming language or even into executable or object code. For instance, a number of programming utilities exist within the art to convert diagrams in Uniform Modeling Language

Docket No. AUS920030165US1

(UML) into source code in "conventional" text-based programming languages, such as Java and C++.

In addition, some programming environments support programming using graphical tools in place of or in addition to conventional text-based source code. For example, the JAVA™ programming language supports an application programming interface (API) called JAVABEANS™. The JAVABEANS™ API enables the creation of highly encapsulated objects (called "beans"), which support introspection and which are executed through an event-driven interface. Although the JAVABEANS™ API may be used for producing conventional text-based source code in the JAVA™ programming language, the JAVABEANS™ API also supports the creation of applications and configuration of "beans" using graphical environments. Thus, graphical program components, such as "beans," and graphically-programmed program code (such as an application utilizing the JAVABEANS™ API) are also considered source code for the purposes of this document.

"Source code feature" or "code feature," in this context, means a portion of a body of source code. A "body of source code," in the present context, means one or more files or other units of program source code.

In the vast majority of cases, a developer will want to associate commentary with code features that are defined by the programming language being used, such as a subroutine (e.g., a function, procedure, method, etc.), object, class, variable, or line or statement of code. In some circumstances, however, a developer may choose to associate a comment with an arbitrary portion of code,

Docket No. AUS920030165US1

such as a portion of a statement, for example. A developer may also wish to associate a comment with one or more source code files in a body of source code.

One particularly significant reason why a developer
5 might want to associate a comment with a language-defined code feature, and in particular a relatively "coarse-grained" feature such as a class or function, is that such features tend to persist over time. For example, specific lines of code in a function may change as a
10 program is developed, but the function may persist. A preferred embodiment enables a developer to associate a comment with a language-defined code feature so that modifications to that code feature, such as deletions of lines of code from the code feature that do not destroy
15 the code feature as a whole, do not also destroy the associated comment.

There are many ways in which association of a comment with a portion of program source code may be accomplished. For example, user **402** might highlight or
20 otherwise select a portion of code in an editor program or IDE, then enter a comment in a special dialog box or window. An exemplary embodiment of the present invention that includes this feature is described in **Figure 15**.

Alternatively, one may enter commentary directly
25 into the text of a source document using special tags or characters to separate comments from program code and to associate particular comments with particular code features. This feature is described in **Figures 13 and 14** with respect to an exemplary embodiment of the present
30 invention utilizing markup language tags.

Docket No. AUS920030165US1

One of ordinary skill in the art will also recognize that many programming languages, such as the JAVA™ programming language, include special symbols or operators for denoting comments (e.g., /* and */ in the C programming language and other related programming languages). The placement of such a comment in a source file in proximity to a particular code feature can indicate an association between the comment and the code feature, as with "javadoc" comments in the JAVA™ programming language. This association by placement is typical of literate programming environments, such as the aforementioned WEB system of Donald Knuth, in which each "section" of a literate program has text and code sub-sections. Another way in which a comment may be associated with a particular code feature is to place associating information within a standard language-supported comment (e.g., placing a string such as "@associate=feature" in an ordinary programming language comment).

In a graphical programming environment, such as a "workbench" for configuring "beans" in the JAVABEANS™ API, or in a modeling environment, such as a UML modeling application, comments may be associated with code features (e.g., a bean) by affixing a graphical feature to a graphical program component and entering text. UML, for example, includes a "comment" symbol that may be affixed to a class or other UML artifact to provide free-form textual commentary. The UML comment symbol has the appearance of a dog-eared paper note, and text may be entered on the "writing surface" of the comment symbol.

Docket No. AUS920030165US1

Once a comment has been associated with a code feature, user **402** can assign access privileges to the comment to allow the comment to be accessed only by intended readers of the comment (use case **406**).

5 Assigning access privileges to source code commentary allows messages to be directed to specific other developers or to groups of developers. Developers who are granted an access privilege to a particular comment will be able to view the comment when viewing the
10 associated source code (e.g., in an IDE, editor, or viewer program). Developers who are not given access privileges to a comment will not be able to read the comment when viewing the associated code feature (assuming, of course, that these "non-privileged"
15 developers can access the actual code feature to begin with).

In one embodiment of the present invention, these "access privileges" may actually be bifurcated into distinct designations of "access privileges" and
20 "intended readers." Specifying both access privileges and intended readers allows for situations in which one or more developers do not necessarily have use for particular information, but might have a possible use for the information in the future. In such instances, those
25 particular developers can be given access privileges to the information, but not designated as intended recipients. The developers would then be able to access the information only if desired.

A key advantage to this feature of providing
30 commentary only to selected readers is that an individual

Docket No. AUS920030165US1

developer is provided with only the information that the developer needs and is not inundated with excessive information having little relevancy to that developer's particular work. This makes communication more
5 efficient, because a developer does not have to spend as much time searching for information that the developer needs for that developer's particular contribution to a project. It also makes communication more effective, because a developer that has less to read is less likely
10 to miss important information by skimming through material in an effort to save time. These advantages of a preferred embodiment of the present invention, although they can be realized in the context of practically any collaborative programming project, are particularly
15 useful when applied in conjunction with eXtreme Programming (XP) or collaborative development over a network (e.g., collaborative open-source development over the Internet).

Also, when the full range of individuals who may
20 view or edit the source code to a software product is considered, the ability to choose a set of intended readers for a particular comment is very useful, because different readers (especially those with non-programming roles) have different informational needs. A number of
25 examples (not intended to be exhaustive) are provided here to suggest the diversity of informational needs that can arise in a particular project. A project manager, for example, may need a high-level view of the project as a whole. A software architect may need a more detailed
30 high-level understanding that reveals how closely the

Docket No. AUS920030165US1

implementation of the software matches the original design. An intellectual property attorney may only be concerned with code excerpts that illustrate a novel process or the practical application of a novel algorithm and may not have any need for much overall design information or low-level details. A user may only need to know where to look in order to configure or extend a software product, and may not have any need to understand low-level implementation details.

10 Commenting system **400** may also be used to send a notification to one or more developers to let those developers know that the comment has been created (use case **408**). In a preferred embodiment, this notification process may be performed by sending an electronic mail or
15 some other form of message (such as an "instant message" that appears on a recipient's desktop, within the recipient's IDE, or to an "instant messaging" client, such as AOL (America Online) INSTANT MESSENGER™, or via some other form of communication (e.g., sending a message
20 to an alphanumeric pager, leaving a voice mail, sending a fax, etc.)). Such a notification may include the particular source code feature that is commented and a copy of the comment (e.g., as an attachment to an electronic mail message), or an indication of where the
25 commented code feature is located (e.g., file names and line numbers), or any other appropriate information for locating and/or displaying the comment and/or the associated source code feature.

 Finally, additional options or constraints may be
30 associated to the comment by user **402** (use case **410**). An

Docket No. AUS920030165US1

example of an additional option that might be incorporated into a comment is a rule concerning how long the comment should exist (use case **412**). For example, a date and/or time for expiration of a comment may be specified. As another example, user **402** could specify that a comment should only exist as a part of a notification message and only as long as the notification message exists (e.g., in the recipient's electronic mail inbox). One of ordinary skill in the art will recognize, then, that a comment may be specified to be persistent, meaning that the comment will be saved to secondary storage (e.g., disk) along with the latest version of the source code, or a comment may be specified as being transient, so that the comment only exists in a notification message and is not recorded in persistent secondary storage.

While many of the advantages of the present invention can be appreciated from the enumerated use cases depicted in **Figure 4**, one of ordinary skill in the art should recognize that the use cases depicted **Figure 4** are not intended to be exhaustive. One of ordinary skill in the art will recognize that additional comment-related functionalities may be provided for in an actual embodiment of the present invention.

Moreover, one of ordinary skill in the art will recognize that even the functionalities described in **Figure 4** are themselves amenable to a wide range of variations in the implementation of such functionalities. As stated previously, a preferred embodiment of the present invention may be incorporated into wide variety

Docket No. AUS920030165US1

of programming tools or embodied in one or more stand-alone tools. **Figures 5-7** are deployment diagrams that illustrate a number of different configurations of software development tools in which the present invention may be embodied. While **Figures 5-7** depict with specificity a number deployments of embodiments of the present invention, it should be noted that the various configurations depicted herein are not intended to be exhaustive of the wide range of architectural and deployment-related variations within the scope and spirit of the present invention.

Figure 5 is a deployment diagram depicting a preferred embodiment of the present invention in which features of present invention are incorporated into integrated development environments (IDEs). User **500** and user **502** are developers in a collaborative software development project. Users **500** and **502** develop source code on network-attached workstations **504** and **506** using IDEs **508** and **510**, respectively. IDEs **508** and **510** store source code in a common code repository **512** associated with a server **514**. Code repository **512**, in a preferred embodiment, may be implemented as a Network File System (NFS) or other shared volume that is mounted by both workstation **504** and workstation **506**. In the embodiment depicted in **Figure 5**, IDEs **508** and **510** are used to edit, compile, and comment source code. Comments are stored in code repository **512** along with the source code, either in separate files for comments and code, or together in a combined file format.

Docket No. AUS920030165US1

Thus, if user **500** creates a comment and associates that comment with a particular source code feature using IDE **508**, when user **500** saves the edited source code, the comment and source code will be saved to code repository **512** along with user **500**'s designation of intended readers of the comment. When the source code is viewed by user **502** via IDE **510**, the comments for which user **502** is an intended reader are displayed by IDE **510** in conjunction with the source code.

Figure 6 is a deployment diagram of a preferred embodiment of the present invention in which a plurality of tools are utilized in place of IDEs. The embodiment depicted in **Figure 6** also utilizes a configuration management system based on a client-server architecture, in which the configuration management system is enhanced to provide commenting features in accordance with the present invention.

In **Figure 6**, developer workstations **600** and **602** each support a suite of software development tools (i.e., components **604-622**, even numbers). With respect to workstation **600**, these tools include an editor program **604** for editing source code, a compiler **608** for compiling source code into object code modules, a linker **612** for linking object code modules into executables, a debugger **616** for monitoring the execution of an executable for the purpose of identifying bugs, and a configuration management client **620**.

In this depicted embodiment, the commenting-related features of the present invention are, for the most part,

Docket No. AUS920030165US1

incorporated into configuration management client **620** and editor program **604**.

Editor program **604** is used to view and edit source code. Editor program **604** allows a user to enter comments
5 to be associated with particular code features and allows a list of intended readers to be associated with the comment as well. As stated previously, this association of a comment to a code feature may be accomplished using various techniques, including inserting comment text or
10 markup tags into a source code text file and entering comment text special commands or graphical means provided by editor program **604**, among others.

Configuration management client **620** is used to check source code in and out of a code repository **628** that is
15 controlled by a configuration management server **624** (software) residing on a server **626** (hardware). When source code that has been annotated with comments by editor program **604** is checked into code repository **628** by configuration management client **620**, the comments are
20 also stored in code repository **628**. When configuration management client **622** is used to retrieve the source code, configuration management server **624** returns the source code along with only those comments for which the user of developer workstation **602** is listed as an
25 intended reader.

Configuration management systems are typically designed to generate desired versions of source code files from stored changes. Such systems are also typically designed to enforce different levels of access
30 privileges for different developers. The implementation

Docket No. AUS920030165US1

of the preferred embodiment depicted in **Figure 6** by enhancing a configuration management system to support access control for comments and to assemble differently commented versions of a source code file for different developers may thus be accomplished by programming the configuration management system to assemble different versions of a source code file according to version-identifying criteria that not only include a version number (as in conventional configuration management systems), but also the identity of the developer requesting the source file.

Figure 7 is a deployment diagram depicting a preferred embodiment of the present invention in which a shared computer system, such as a single server or timesharing system, is utilized as the hardware platform. Shared computer system **700** is operated by users **702** and **704**. User **702** and user **704** have separate IDE processes **706** executing on shared computer system **700**. IDE processes **706** share a common code storage facility **708**, which may be, for example, an attached hard disk drive or other secondary storage device. One of ordinary skill in the art will recognize that IDE processes **706** may be replaced with processes executing other development tools, such as development tools in a suite of development tools, as well (e.g., as in **Figure 6**).

Figure 8 is a deployment diagram illustrating architecture utilized in a preferred embodiment of the present invention for notifying an intended reader of a comment that the comment is available. A developer workstation **800** supports an IDE **802**, which is used to

Docket No. AUS920030165US1

create and display comments in accordance with a preferred embodiment of the present invention. IDE **802** communicates with an e-mail client program **804**, which is also deployed on developer workstation **800**. E-mail client **804** allows electronic mail messages to be transmitted over network **806**. When a user creates a comment using IDE **802**, IDE **802** uses e-mail client **804** to transmit an electronic mail message to the intended readers of the comment to notify the intended readers that the comment is available. This electronic mail message may include actual source code and comment text or it may contain other information, such as a file names and locations, to allow the intended reader to locate the comment and associated source code.

For example, assume that developer workstation **810** is the workstation of an intended reader of a comment created by the user of developer workstation **800**. E-mail client **808**, which resides on developer workstation **810**, will receive an electronic mail message as a notification. In a preferred embodiment, E-mail client **808** may be programmed to forward the received notification message to IDE **812** on developer workstation **810**. IDE **812** can then display the comment and associated source code portion for the user of developer workstation **810**.

Several variations on the notification scheme depicted in **Figure 8** may be utilized in place of or in addition to the features described in **Figure 8**. For example, although **Figure 8** shows separate IDE and E-mail client processes, one of ordinary skill in the art will

Docket No. AUS920030165US1

recognize that a single program may be used for both editing source code and comments and for sending mail. For example, the open-source EMACS text editor supports electronic mail features as well text-editing

5 capabilities. Alternatively, more specialized tools, such as command-line driven programming tools, may be utilized instead of an IDE.

The particular protocol through which notification messages are transmitted may differ as well. For
10 example, some form of instant messaging or chat protocol may be used in place of or in addition to electronic mail. Other physical media, such as telephone-based messaging or facsimile may be used, as well. One of
15 ordinary skill in the art will recognize that a wide variety of communications media may be employed to provide notification capabilities without departing from the scope and spirit of the present invention.

Figures 9-12 concern the storage and retrieval of comments and source code. **Figure 9** is a collaboration
20 diagram that provides a general overview of the actions performed by a preferred embodiment of the present invention. In **Figure 9**, user **900** enters commentary into an IDE **904** (or other suitable program, as discussed above) (action **1**). User **900** associates the entered
25 commentary with a source code feature (action **2**). A set of intended readers is also specified by user **900** (action **3**). IDE **904** stores the commentary and associated source code to secondary storage **908** (action **4**). In one embodiment, storage and retrieval to/from secondary

Docket No. AUS920030165US1

storage **908** is controlled by a configuration management system.

User **902**, who we will assume is an intended reader of the comment, opens the source code for editing or
5 viewing using IDE **906** (action **5**). IDE **906** then requests the code from secondary storage **908** (action **6**). Storage **908** returns the requested code (action **7**) and the associated commentary (action **8**). IDE **906** then displays the requested code **906** (action **9**) and also the associated
10 commentary (assuming, of course, that user **902** is an intended reader of the commentary) (action **10**).

Figures 10-12 describe a number of possible storage and retrieval schemes for performing the actions described in **Figure 9**. **Figures 10-12** are not intended to
15 provide an exhaustive catalog of all possible schemes that may be employed in an embodiment of the present invention. Rather **Figures 10-12** merely exemplify how storage and retrieval of comments and associated source code may be achieved in the context of the present
20 invention. One of ordinary skill in the art will recognize that the examples provided here suggest a wide range of variations in the way comments and associated source code may be stored and retrieved within an embodiment of the present invention.

Figure 10 is a diagram depicting a process of
25 storing commentary in an embodiment of the present invention in which source code and commentary are stored separately in secondary storage. User **1000** writes source code **1004** with which user **1000** associates commentary
30 (action **1002**). User **1000** enters the source code and

Docket No. AUS920030165US1

commentary into an IDE **1006** (which could alternatively be a suite of development tools), which supports private source code comments in accordance with a preferred embodiment of the present invention.

5 IDE **1006** produces from commented source code **1004** a source code document **1012** (action **1008**) and a commentary document **1014** (action **1010**). One of ordinary skill will recognize that source code document **1012**, consisting of only source code, can be compiled or interpreted by any
10 compiler or interpreter for the language the source code is implemented in. Source code document **1012** is stored in secondary storage **1016**.

Commentary document **1014** contains commentary and association data to allow the commentary to be associated
15 with source code features contained within source code document **1012**. A document containing existing commentary **1020** is retrieved from secondary storage **1016** (action **1018**). The commentary from commentary document **1014** is merged with existing commentary document **1020** to form a
20 merged commentary document **1024** (action **1022**), which is then stored in secondary storage **1016** (action **1026**).

Figure 11 is a diagram depicting a reverse process with respect to the process described in **Figure 10**, in accordance with a preferred embodiment of the present
25 invention. **Figure 11** depicts a process of displaying selected commentary to an intended reader, user **1116**. Source code document **1100** and merged commentary document **1106** are retrieved from secondary storage. Since merged commentary document **1106** contains a composite set of
30 comments for different sets of intended readers, merged

Docket No. AUS920030165US1

commentary document **1106** is filtered (action **1108**) to obtain a filtered commentary document **1110** containing only comments for which user **1116** is an intended reader. Filtered commentary document **1110** is then loaded (action
5 **1112**) into IDE **1104** along with source code document **1110** (action **1102**) for display to user **1116** (action **1114**).

In an alternative embodiment, source code and comments may be stored in a single file. **Figure 12** depicts a process of processing a combined code/comment
10 file **1200** for display and compilation of source code and comments by a developer. Combined file **1200** is filtered to remove from combined file **1200** comments that do not pertain to the developer (action **1202**), thereby obtaining a filtered combined commentary and source code document
15 **1204**. Combined document **1204** may then be formatted (action **1210**) to obtain commented source code in a format suitable for display (action **1212**).

Combined file **1200** may also be filtered to remove all of the commentary (action **1206**) and thus obtain clean
20 source code **1208** suitable for compilation or interpretation. For example, clean source code **1208** may be compiled (action **1214**) to obtain relocatable or executable object code **1216**.

Figures 13-16 concern the entry and display of
25 private source code comments in accordance with a preferred embodiment of the present invention. **Figures 13 and 14** depict a comment and source code format utilizing tags in a markup language to associate comments with source code features.

Docket No. AUS920030165US1

Figure 13 is a diagram of an excerpt from a combined source code and commentary document made in accordance with a preferred embodiment of the present invention utilizing markup language tags for associating comments with source code features. In this example, the markup language that is used is eXtensible Markup Language (XML), although any one of a number of markup languages may be used without departing from the scope and spirit of the present invention. "Commented" tags **1300** and **1302** denote that source code statement **1303** is associated with commentary. Comment tags **1304** and **1306**, which are nested within tags **1300** and **1302**, enclose a single comment. The label of tags **1304** and **1306** denote the intended reader of the comment (Kulvir). Tags **1310** and **1312**, labeled "mike-kulvir" enclose a comment that is intended to be read by both Mike and Kulvir (i.e., two intended readers). When the source code/commentary excerpt is displayed to a developer, the comments will be filtered, so that only comments directed to the intended readers will be displayed.

In a preferred embodiment, groups of intended readers may be specified by listing the members of the group or by referring to the group by name. For example, in the example source code/commentary excerpt provided in **Figure 14**, tags **1408** and **1410** enclose a comment that is intended to be read by anyone reading the source code. Additional options or constraints for comments may be included, as well. Tag **1400** of **Figure 14** includes an additional attribute **1404** that denotes an expiration date for the comment enclosed by tags **1400** and **1402**.

Docket No. AUS920030165US1

Figures 15 and **16** describe the entry of comments into a source code file being edited in windowed IDE in accordance with a preferred embodiment of the present invention. Window **1500** represents the main window for an IDE in a windowed graphical user interface (GUI). A pointing device cursor **1501** is used to select text and actuate components in window **1500**. Editing area **1502** is used to edit source code text. Additional controls are provided for accessing other development features.

Comment button **1504** allows the entry of comments in accordance with a preferred embodiment of the present invention (q.v.). Compile button **1506** allows the source code in the IDE to be compiled. Run button **1508** allows the program represented by the source code in the IDE to be executed.

In this example, a developer may associate a comment with a particular code feature by selecting (highlighting) the particular code feature with pointing device cursor **1501**, as with selected code feature **1510**, then actuating comment button **1504**. A commentary entry box **1512** is then displayed with a cursor **1514** provided for the entry of commentary text. Once the commentary text has been entered (signified, for example, by the developer's pressing the "enter" or "return" key on the workstation's keyboard), an additional dialog box is displayed, as depicted in **Figure 16**.

Figure 16 is a diagram of a dialog box **1604** for entering one or more intended readers of a source code comment **1602** associated with source code **1600** in an IDE implemented in accordance with a preferred embodiment of

Docket No. AUS920030165US1

the present invention. List **1606** provides a list of possible intended readers or groups of intended readers. In this preferred embodiment, the possible intended readers and groups of intended readers in list **1606** may
5 be extracted from a directory service, such as a directory service based on the Lightweight Directory Access Protocol (LDAP), which allows hierarchical directory structures to be created, modified, and accessed. The developer selects the intended readers by
10 highlighting (e.g., highlight bar **1608**) the desired selections and actuating "OK" button **1612**. Additional controls may be provided for other options, such as electronic mail or instant messaging notification. For example, in **Figure 16**, dialog box **1604** includes
15 radiobuttons **1610** and **1611** for allowing electronic mail- or instant messaging-based notification of new comments.

In a preferred embodiment of the present invention, when an intended recipient of a comment views that comment, it comment is highlighted, so as to make that
20 intended recipient aware that the comment is a comment that is not necessarily available to all readers of the source code.

Figure 17 is a flowchart representation of an overall process of private source code messaging in
25 accordance with a preferred embodiment of the present invention. A user enters a comment (block **1700**), which the user associates with a code feature (block **1702**). Then, the user associates a list of intended readers with the comment (block **1704**). If the user intends for the
30 readers to be notified of the comment (block **1706:Yes**), a

Docket No. AUS920030165US1

notification (e.g., via electronic mail or instant
messaging) is sent to the readers (block **1708**). After
sending the notification or determining that notification
is not desired, the comment is stored along with the
5 source code (e.g., in a configuration management system).

It is important to note that while the present
invention has been described in the context of a fully
functioning data processing system, those of ordinary
skill in the art will appreciate that the processes of
10 the present invention are capable of being distributed in
the form of a computer readable medium of instructions or
other functional descriptive material and in a variety of
other forms and that the present invention is equally
applicable regardless of the particular type of signal
15 bearing media actually used to carry out the
distribution. Examples of computer readable media
include recordable-type media, such as a floppy disk, a
hard disk drive, a RAM, CD-ROMs, DVD-ROMs, and
transmission-type media, such as digital and analog
20 communications links, wired or wireless communications
links using transmission forms, such as, for example,
radio frequency and light wave transmissions. The
computer readable media may take the form of coded
formats that are decoded for actual use in a particular
25 data processing system. Functional descriptive material
is information that imparts functionality to a machine.
Functional descriptive material includes, but is not
limited to, computer programs, instructions, rules,
facts, definitions of computable functions, objects, and
30 data structures.

Docket No. AUS920030165US1

The description of the present invention has been presented for purposes of illustration and description, and is not intended to be exhaustive or limited to the invention in the form disclosed. Many modifications and
5 variations will be apparent to those of ordinary skill in the art. The embodiment was chosen and described in order to best explain the principles of the invention, the practical application, and to enable others of ordinary skill in the art to understand the invention for
10 various embodiments with various modifications as are suited to the particular use contemplated.